



Specific polishing compounds for each product/application

Aluminium

Type of compound	Description	Colour	Process	Cut rate	Shine level	Grease level	Buff Recommended
Liquid	1600	Grey	Cut	10	3	7	Impregnated Sisal
Liquid	1625	Cream	Cut	9	4	6	Sisal
Liquid	1425	White	Cut / Shine	7	6	5	Impregnated Cotton
Liquid	RN-552	Brown	Cut / Shine	6	7	7	Cotton
Liquid	5980	White	Shine	2	10	1	Cotton / Flannel
Solid	Num 14 B	Grey	Cut	10	3	7	Sisal
Solid	Grauer K	Brown	Cut / Shine	6	7	5	Cotton
Solid	Num 34	Brown	Cut / Shine	7	6	7	Cotton
Solid	RN-043	Brown	Cut / Shine	6	7	5	Cotton
Solid	Símil Gewelia	Brown	Cut / Shine	6	6	7	Cotton
Solid	Latinox	White	Shine	3	9	2	Cotton / Flannel
Solid	Vebrix	Green	Shine	4	9	2	Cotton / Flannel

Level 10 : maximum

Level 0 : minimum

Packaging

Liquid Compounds 50 Kg boxes, 250 Kg. metal barrels and 1,000 and 1,300 Kg containers.

Solid Compounds 28 tablet boxes, the weight varies depending on the type of compound.
Approx. 28-34 Kg.

Format Standard - Bars of 200*50*50 mm.
Special sizes available on demand.